

# ANTI-GRAFFITI PRODUCTS

**KEIM MX Glaze** - KEIM MX Glaze is an engineered siloxane coating with the properties of both a high performance epoxy and a polyurethane in one coat.

KEIM MX Glaze provides a general purpose high gloss, clear coating which has good weathering and wear resistance properties.

The finish provides a wipeable, durable surface that has excellent anti-graffiti properties and is suitable for all mineral substrates.

KEIM MX Glaze can be applied over KEIM Mineral Paints to provide anti-graffiti protection.

**KEIM Wax Coating** - KEIM Wax Coating is a sacrificial anti-graffiti system applied as a two coat system.

KEIM Wax Coating is made with polymers and synthetic water-based wax and is designed to be easily removed and re-applied. Graffiti can be removed using a high pressure sprayer or by using KEIM Wax Coating Graffiti Cleaner.

KEIM Wax Coating has a low sheen finish and does not significantly darken the surface to which it is applied. It is suitable for all mineral surfaces and for surfaces which have been treated with KEIM Mineral Paints.



# ANTI-GRAFFITI TECHNICAL INFORMATION

Product	KEIM Glaze MX	KEIM Wax Coating
<b>1. Field of Application</b>	KEIM MX Glaze is an engineered siloxane coating with the properties of both a high performance epoxy and a polyurethane in one coat. General purpose high gloss coating offering good weathering and wear resistance. Provides a wipeable, durable surface that has good anti-graffiti properties for all mineral substrates.	KEIM Wax Coating is a two coat semi-permanent/sacrificial anti-graffiti system made from polymers and water-based wax. KEIM Wax Coating is suitable for all mineral surfaces and for surfaces which have been treated with KEIM Mineral Paints.
<b>2. Product Properties</b>	<ul style="list-style-type: none"> <li>• Gloss appearance</li> <li>• Easy to remove graffiti</li> <li>• Clear</li> </ul>	<ul style="list-style-type: none"> <li>• Non-flammable</li> <li>• Easy to remove graffiti and recoat</li> <li>• High vapour permeability</li> <li>• Clear</li> </ul>
<b>3. Application Instructions (onto clean dry surfaces)</b>	KEIM MX Glaze is supplied in the correct mixing proportions of resin and cure. Add cure to resin and stir thoroughly with mechanical mixer for five minutes. Apply a thin and even coat by brush or short pile roller.	KEIM Anti-Graffiti Wax Coating should be applied as a two coat system with four hours between coats. Each coat is applied working from the top downwards by low-pressure spray, brush or roller.
<b>Cleaning of tools</b>	Clean immediately after use with solvent.	Clean immediately after use with water.
<b>Consumption*</b>	Approx. 0.1lt/m <sup>2</sup> per coat	Approx. 0.25 - 0.3 lt/m <sup>2</sup> (for two coats)
<b>Packaging</b>	5 lt containers	5 lt containers

\*Please note all consumption rates given in the technical information section are offered for guideline purposes and are quoted for smooth surfaces. Actual rates are the responsibility of the applicator. Project specifications should be referred to for specific rates.